

Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-200
Scheme:	(A) Vibrant	Item Name:	Side Table Lamp - REQUIRED VENDOR/DESIGN
Issue Date:	March-23	Area Name:	Guest Suite
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Round Table Lamp with Round Base and Tapered	d Shade	
Dimensions:	6" Dia.(at Base) x 10"D x 21"H		
Finish:	Lamp body and finial to match RAL 9011 Graphit finish, Base finish to match Tiger Drylac Sparkle		0
Switch Type:	On/Off Accessible rocker switch at base, Finish: I	Black	
Cord Length:	72"		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Lamp Type:	A15 LED, E26 Medium Socket, 2700K		
Lamp Wattage:	8.5W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diffuser Style:	Tapered drum shade		
Shade/Diff. Material:	White linen wrapped shade with rolled edges		
Shade/Diff. Dims.:	Top: 9 1/2" Dia.; Bottom: 11 3/4"; Dia.; Height	: 10"	
Lamp Base:	Base to feature felt protective non-skid padding s Base to be weighted.	secured to bottom.	Lamp Body & Finial Finish
Dimmer:	No		
Notes:	NA		Base Finish

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety,
- UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-201
Scheme:	(A) Vibrant	Item Name:	Desk Lamp - REQUIRED VENDOR/DESIGN
Issue Date:	March-23	Area Name:	Guest Suite
Revisions:	May-23 Δ1; Dec-23 Δ4; APR-24 Δ5; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Lamp at Desk		
Dimensions:	6" Dia Base x 11 1/2"D x 18"H		
Finish:	Overall Lamp Body & Base: To match RAL #170 40		
Switch Type:	Accent Banding: To match RAL 9011 Graphite Black On/Off Accessible rocker switch at base, Finish: Blac		A
Cord Length:	72"		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Lamp Type:	A15 LED, E26 Medium Socket, 2700K		and the second division of the second divisio
Lamp Wattage:	10W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diffuser Style:	Fixed shade with diffuser at top		
Shade/Diff. Material:	Frosted, matte, white acrylic shade		& Base Finish Accent Finish
Shade/Diff. Dims.:	5" Dia. x 8" H	Lamp Body	& Base Finish Accent Finish
Lamp Base:	Base to feature felt protective non-skid padding secu Base to be weighted.	ured to bottom.	
Dimmer:	No		
Natari	NA		
Notes:	NA		

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-202
Scheme:	(A) Vibrant	Item Name:	Nightstand Sconce - REQUIRED VENDOR/DESIGN
Issue Date:	March-23	Area Name:	Guest Suite
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Wall Mounted Sconce at Nightstand		
Dimensions:	6" Dia. x 4"D x 9", OAH 33"		
Finish:	Overall Back Plate and Stem: To match Tiger Dry Glossy 49/90450	lac Sparkle Silver	
Switch Type:	On/Off Accessible Rocker switch at stem, Finish:	Black	
Cord Length:	72" from exit to plug		Pi T
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Cord Cover:	Provide cord cover, finish to match Tiger Drylac S 49/90450. Cord cover length 24".	parkle Silver Glossy	
Lamp Type:	Replaceable LED Board, 2700K		
Lamp Wattage:	10W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diffuser Style:	Round; Twist on		
Shade/Diff. Material:	Frosted, matte, white acrylic shade		Overall Finish
Shade/Diff. Dims.:	3"D x 6"H		
Installation Type:	Wall mounted. Mounting plate to be provided by	manufacturer.	
Suspension Info:	$\Delta 9$ See prototype plan set for mounting heights/	locations	
Dimmer:	No		
Notes:	NA		

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-203
Scheme:	(A) Vibrant	Item Name:	Vanity Sconce - REQUIRED VENDOR/DESIGN
Issue Date:	March-23	Area Name:	Guest Suite
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Wall Sconce at Vanity		
Dimensions:	48" W x 2.5" D x 5" H		
Finish:	Overall to match Tiger Drylac Sparkle Silver Glossy 49/90450		
Switch Type:	Hardwired		u
Cord Length:	NA		
Cord Color:	NA		The state of the second s
Lamp Type:	Replaceable LED Board, 3000K		
Lamp Wattage:	24W		
Lamp Quantity:	1	19	
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diffuser Style:	Rectangular; Fastener attached	1	
Shade/Diffuser Style:	Tapered drum	0	verall Finish
Shade/Diff. Material:	Frosted, matte, white acrylic shade		
Shade/Diff. Dims.:	2" D x 1 1/2" H x 48"L		
Suspension Info:	Refer to architectural drawings		
Dimmer:	No		
Notes:	Manufacturer to provide mounting hardware. Coordi location of j-box and architectural field conditions.	inate location of	fixture's electrical feed with

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-204
Scheme:	(A) Vibrant	Item Name:	Sconce @ Wall Hooks -
Issue Date:	March-23		REQUIRED VENDOR/DESIGN
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9	Area Name:	Guest Suite
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Casegood Mounted, Corded Sconce with Accent Trin	n	
Dimensions:	Overall: 7 3/4" D x 5" W x 10 7/16" H, Back Plate	Max. Height: 4.5" H	·
Finish:	Overall: To match Tiger Drylac Sparkle Silver Glossy Banding: To match RAL 9011 Graphite Black in mat		
Switch Type:	On/Off Accessible Rocker switch located at lower sic Finish: Black		
Cord Length:	Δ9 96"		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Lamp Type:	A15 LED, E26 Medium Socket, 2700K		
Lamp Wattage:	8.5W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diffuser Style:	Fixed shade with acrylic top and bottom diffuser		
Shade/Diff. Material:	Frosted, matte, white acrylic shade		Overall Finish
Shade/Diff. Dims.:	4" Top Dia., 5" Bottom Dia. x 6" H		
Suspension Info:	Coordinate with Working Wall and refer to architect	ural drawings	
Dimmer:	No		
Notes:	NA		
			Accent Finish

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-205
Scheme:	(A) Vibrant	Item Name:	Floor Lamp - REQUIRED VENDOR/DESIGN
Issue Date:	March-23	Area Name:	Guest Suite
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Hook Style Lamp with Angled Shade and Round Bas	e	
Dimensions:	12"W x 17"D x 60"H		
Finish:	Overall: To match RAL 9011 Graphite Black in matte	e finish	
Switch Type:	On/Off Accessible mini rocker base switch on stem, above finished floor. Finish: Black	36" on center	
Cord Length:	72"		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Lamp Type:	A19 LED, E26 Medium Socket, 2700K		
Lamp Wattage:	10W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Material:	White linen wrapped shade with rolled edges		
Shade/Diff. Dims.:	Top: 9 1/2" Dia.; Bottom: 11 3/4" Dia.; 14"H		
Lamp Base:	Base to feature felt protective non-skid padding second Base to be weighted.	ured to bottom.	
Dimmer:	No		
Notes:	NA		Lamp Body Finish

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name: Scheme:	Home2 FF&E Specifications (A) Vibrant	Item Number: Item Name:	(A) GR-206 Table Lamp @ Accessible Working Wall - REQUIRED VENDOR/DESIGN
Issue Date:	March-23	Area Name:	Guest Suite
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Cylinder Style Lamp with Ring Accents and a To	p Shade	
Overall Dimensions:	6"Dia. (at Base) x 12" D x 23"H		
Finish:	Lamp Body and Finial: To match RAL 9011 Grap finish	phite Black in matte	
Switch Type:	On/Off Accessible rocker switch at base, Finish:	Black	
Cord Length:	60"		
Cord Color:	Clear/Silver		\leq
Plug Type:	90° plug with 45° cord placement		
Lamp Type:	A15 LED, E26 medium socket 2700K		
Lamp Wattage:	7-10W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Style:	Tapered drum		
Shade/Diff. Material:	White linen wrapped shade with rolled edges		
Shade/Diff. Dims.:	Top: 11" Dia.; Bottom: 12"Dia.; Height: 10"		
Lamp Base:	Base to feature felt protective non-skid padding Base to be weighted.	secured to bottom.	Lamp Body & Fnial Finish
Dimmer:	No		
Notes:	Provide integrated cord management concealed	in lamp base.	

Instructions:

• All quantities to be verified by hotel operator prior to purchasing.

• It is the responsibility of the owner to interpret these specifications for each property.

• All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.

- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name: Scheme: Issue Date:	Home2 FF&E Specs (A) Vibrant March-23	Item Number: Item Name:	(A) GR-207 Nightstand Sconce @ Queen Queen Center - REQUIRED VENDOR/DESIGN
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9	Area Name:	Guest Suite
Manufacturer:	Email: Δ9	Phone: $\Delta 9$	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Wall Mounted Sconce at Nightstand with 2 Sconce Sconce Stem Join to Become One Plug-in Cord	es, Cords from Each	
Dimensions:	20"OAW x 33" OAH, Each 6" Dia. x 4"D x 9" H		
Finish:	Overall: To match Tiger Drylac Sparkle Silver Glos	-	
Switch Type:	On/Off Accessible Rocker switch at stems, Finish:	Black	
Cord Length:	72" from join to plug		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Cord Cover:	Provide cord cover, finish to match Tiger Drylac Sp 49/90450. Cord cover length 24".	parkle Silver Glossy	
Lamp Type:	Replaceable LED Board, 2700K		
Lamp Wattage:	10W each, 20W total		<u>``</u>
Lamp Quantity:	2 (1 per shade)		Ĭ
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Material:	Frosted, matte, white acrylic shade		and the state of the second second second
Shade/Diff. Dims.:	3"D x 6"H		
Installation Type:	Wall mounted. Mounting plate to be provided by	manufacturer.	
Suspension Info:	$\Delta 9$ See prototype plan set for mounting heights/ k	ocations	
Dimmer:	No		
Notes:	NA		
			Overall Finish

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-250
Scheme:	(A) Vibrant	Item Name:	Nightstand Lamp - RENO ONLY
Issue Date:	May-23		
Revisions:	June-23 Δ2; Dec-23 Δ4; Sept-24 Δ9	Area Name:	Guest Suite
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Cylinder Style Lamp with Ring Accents and a Top	Shade	600
Dimensions:	7" Dia. (at Base) x 12"D x 23"H		
Finish:	Lamp Body & Finial: To match RAL 9011 Graphite finish, Base: To match Tiger Drylac Sparkle Silver		
Switch Type:	On/Off Accessible rocker switch at base, Finish: B	lack	
Cord Length:	72"		
Cord Color:	Clear/Silver		\sum
Plug Type:	90° plug with 45° cord placement		$\langle - \rangle$
Lamp Type:	A15 LED, E26 medium socket 2700K		
Lamp Wattage:	8.5W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diffuser Style:	Tapered drum shade		
Shade/Diff. Material:	White linen wrapped shade with rolled edges		
Shade/Diff. Dims.:	Top: 11" Dia.; Bottom: 12"Dia.; Height: 10"		
Lamp Base:	Base to feature felt protective non-skid padding se Base to be weighted.	ecured to bottom.	Lamp Body & Finial
Dimmer:	No		
Notes:	Two outlets and 1USB-A and 1 USB-C ports to be base.	integrated into the	
			Base Finish

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety,
- UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-251
Scheme:	(A) Vibrant	Item Name:	Side Table Lamp @ Sofa -
Issue Date:	May-23		RENO ONLY
Revisions:	Dec-23 Δ4; Sept-24 Δ9	Area Name:	Guest Suite
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Round Table Lamp with Round Base including Outl Shade	ets and Tapered	
Dimensions:	7" Dia.(at Base) x 10"D x 21"H		
Finish:	Lamp Body & Finial: To match RAL 9011 Graphite finish, Base: To match Tiger Drylac Sparkle Silver G		
Switch Type:	On/Off Accessible rocker switch at base, Finish: Bla	ick	
Cord Length:	72"		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Lamp Type:	A15 LED, E26 Medium Socket, 2700K		
Lamp Wattage:	8.5W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diffuser Style:	Fixed drum shade		
Shade/Diff. Material:	White linen wrapped shade with rolled edges		
Shade/Diff. Dims.:	Top: 9 1/2" Dia.; Bottom: 11 3/4"; Dia.; Height: 1	LO"	
Lamp Base:	Base to feature felt protective non-skid padding see Base to be weighted.	cured to bottom.	Lamp Body & Finial Finish
Dimmer:	No		a transfer to the state of the second
Notes:	Two outlets and 1USB-A and 1 USB-C ports to be in base.	ntegrated into the	
			A CONVERTING THE HARDEN

Base Finish

REQUIRED VENDOR, REQUIRED DESIGN

Instructions:

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.

• Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-251
Scheme:	(A) Vibrant	Item Name:	Side Table Lamp @ Sofa -
Issue Date:	May-23		RENO ONLY
Revisions:	Dec-23 Δ4; Sept-24 Δ9	Area Name:	Guest Suite

• Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 FF&E Specs	Item Number:	(A) GR-252
Scheme:	(A) Vibrant	Item Name:	Headboard Sconce - RENO ONLY
Issue Date:	May-23		
Revisions:	Dec-23 ∆4; Apr-24 ∆5; Sept-24 ∆9	Area Name:	Guest Suite
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Headboard Mounted Replacement Sconce		
Dimensions:	6"W x 13"H x 5"D, Backplate: 6"W x 15"H x 1" D		r x
Finish:	Backplate to match RAL 9011 Graphite Black in mat	te finish	
Switch Type:	On/Off Accessible rocker switch at bottom portion of Finish: Black	of back plate,	\sim
Cord Length:	96"		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		_
Lamp Type:	Replaceable LED Board, 2700k		
Lamp Wattage:	10W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Material:	Frosted, matte, white acrylic shade		
Shade/Diff. Dims.:	4"D x 6"H		
Installation Type:	Headboard mounted. Mounting plate to be provided	by manufacturer.	Backplate Finish
Dimmer:	No	,	

Notes:

NA

REQUIRED VENDOR, REQUIRED DESIGN

Instructions:

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- · Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety,

UL standards, and any other specifications that are required to comply with local and state fire codes.

- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name: Scheme: Issue Date:	Home2 FF&E Specs (A) Vibrant Sept-24	Item Number: Item Name:	(A) GR-253.ALT Hardwired End Wall Sconce REQUIRED VENDOR/DESIGN
Revisions:		Area Name:	Guest Suite
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description: Dimensions: Finish:	Wall Mounted, Sconce with Accent Trim Overall: 7 3/4" D x 5" W x 10 7/16" H, Back Plate M Overall: To match Tiger Drylac Sparkle Silver Glossy Banding: To match RAL 9011 Graphite Black in matt	49/90450, Accent	
	Hardwired; Wall Switch A15 LED, E26 Medium Socket, 2700K 8.5W 1 Fixture must be U.L. listed and so labeled Fixed shade with acrylic top and bottom diffuser Frosted, matte, white acrylic shade 4" Top Dia., 5" Bottom Dia. x 6" H Refer to architectural drawings and Renovation Guide No NA	Đ	Overall

Accent Finish

REQUIRED VENDOR, REQUIRED DESIGN

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name: Scheme: Issue Date:	Home2 FF&E Specs (A) Vibrant June-23	Item Number: Item Name: Area Name:	(A) GR-501 ALT Vanity Mirror - Lighted Guest Suite
Revisions:	Sept-24 ∆9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Majestic Mirror	info@majesticmirror.com	305.827.2661	
Description: Style: Dimensions: Edge: Switch Type: Lamp Type:	Backlit Mirror at Bathroom Custom Strand with 4-Sided Frame of Light 42" W x 36"H x 2.125"D Polished Hardwired Gen 2 premium bendable strips, included from		
Mirror Backing: Orientation: Mounting Height:	manufacturer Vinyl Safety Backing Horizontal See Prototype Drawings		

Notes:	Refer to prototype drawings for the exact placement of the backlit mirror. Coordinate location of
	fixture's electrical feed with location of J-box and architectural field conditions.

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample**

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.06

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes for use in hotels and other public spaces, and Brand Standards.
- Provide all parts, pieces and instructions for complete installation. Mounting method to be sufficient for weight of piece.
- All pieces must be crated for shipping. All corners should be wrapped with corner guards. Crates should be labeled with instructions for shipment, storage and opening of crate.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.
- Reference the Design Intent drawings on designinformation.hilton.com for further information.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) OF-717
Scheme:	A-Vibrant	Item Name:	String Lights @ Outdoor
Issue Date:	March-23	Area Name:	Outdoor - Lounge, Grilling Patio,
Revisions:	June-23 Δ2, Dec-23 Δ4		& Pool
Manufacturer:	HD Supply		
Phone:	800-431-3002		
E-mail:	piteamhilton@hdsupply.com		
Web:	www.hdsupplysolutions.com		
Description:	Commercial Grade LED String Lights Set. Includes Decorative LED Bulbs	s (15) Sockets Dist	tanced 2-Feet Apart with (15) Clear
Model Name/No.:	A1V17/SL30-15/FIL Commercial Grade FEIT 30'-0' Lights	LED #S14 Stri	
Dimensions:	364" L x 17" H, Bulbs included		
Finish:	Black		
Switch Type:	Plug-in		
Lamp Type:	E26 Medium Base - 120V Amber Bulb finish		The second second
Lamp Wattage:	LED - SMD/Color Tem: 2200/CRI: 80/ 15,000 hou	ır life span	
Lamp Quantity:	15 Bulbs		
UL Listing:	CETLUS Safety Rating Listed for Damp Locations		
Dimmer:	Non-dimming		
Color Temperature:	2200K		
Notes:	Refer to prototype drawings for location.		
	15 Bulbs included, must order in multiples of (4).		

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample** Shop Drawing

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.03 Instructions:

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-201
Scheme:	A-Vibrant	Item Name:	Pendant Lighting @ Focus Booth
Issue Date:	March-23	Area Name:	Public Area - Lobby
Revisions:	May-23 Δ1; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Hardwired Pendant		Ē
Overall Dimensions:	27" Dia. x 16"H x 36"OH, Canopy 8" Dia.		
Finish:	Exterior: Powder-coated stainless steel to match		
	Celery White matte finish. Interior: To match RA	L 9010 Pure White	
Switch Type:	Hardwired		
Cord Length:	72", adjustable in field		
Cord Color:	Black cloth cord cover		
Lamp Type:	A15 LED, E26 Medium Socket 3000K Dipped Bulb)	
Lamp Wattage:	11W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Style:	Bell shape shade, open at bottom		
Shade/Diff. Material:	Powder-coated stainless steel		
Shade/Diff. Dims.:	27"Dia. x 14"h		Exterior Finish
Suspension Info:	Refer to architectural drawings for mounting heig	tht and location	
Notes:	Manufacturer to provide mounting hardware and		

Interior Finish

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample** Shop Drawing

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-202
Scheme:	A-Vibrant	Item Name:	Bathroom Vanity Light
Issue Date:	March-23	Area Name:	Public Area - Bathroom
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Bathroom Sconce Vanity Light with Square Backplat	e	
Overall Dimensions:	24"W x 5"H x 2 1/2"D		
	Backplate: 7"W x 5"H		
Finish:	Overall: Stainless steel metal powdercoated to mate	h RAL 9011 Graph	nite Black matte finish
Switch Type:	Hardwired		
Cord Length:	NA		
Cord Color:	NA		
Lamp Type:	15W LED board 3000K		
Lamp Wattage:	15 W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and labeled		
Shade/Diff. Style:	Cylinder		
Shade/Diff. Material:	Top: Frosted white matte acrylic and powdercoated metal, Bottom: Powdercoated stainless steel metal	stainless steel	
Shade/Diff. Dims.:	24"W x 1 1/2"D x 1 1/2"H		
Mounting Instructions:	Wall mounted, refer to architectural drawings for m	ounting height	Overall Finish
Notes:	Manufacturer to provide mounting hardware and ac	cessories	

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample** Shop Drawing

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-203
Scheme:	A-Vibrant	Item Name:	Floor Lamp
Issue Date:	March-23	Area Name:	Public Area - TV Lounge
Revisions:	May-23 Δ1; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Hook Style Lamp with Angled Shade and Round	Base	
Overall Dimensions:	12"W x 17"D x 60"H		
Finish:	Overall : To match RAL 9011 Graphite Black in r	natte finish	
Switch Type:	On/Off Accessible mini rocker base switch on ste above finished floor. Finish: Black	em, 36" on center	
Cord Length:	72"		-
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Lamp Type:	A15 LED, E26 Medium Socket, 2700K		
Lamp Wattage:	10W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Style:	Tapered drum		
Shade/Diff. Material:	White linen wrapped shade with rolled edges		
Shade/Diff. Dims.:	Top: 9 1/2" Dia.; Bottom: 11 3/4" Dia.; 14"H		
Lamp Base:	Base to feature felt protective non-skid padding Base to be weighted.	secured to bottom.	
Dimmer:	No		Lamp Body Finish
Notes:	NA		

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample** Shop Drawing

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-204
Scheme:	A-Vibrant	Item Name:	Wall Sconce
Issue Date:	March-23	Area Name:	Public Area - Guest Corridors
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Direct/Indirect Wall Sconce		
Overall Dimensions:	Overall Width: 5"W; 14"H x 4" Max Depth		
Finish:	Backplate & Base: Metal powder-coated to mate Black matte finish	h RAL 9011 Graphite	
Switch Type:	Hardwired		
Cord Length:	NA		$\langle \gamma \rangle$
Cord Color:	NA		
Lamp Type:	LED E26 medium socket 3000K with 360 degree	light output	
Lamp Wattage:	11 W		
Lamp Quantity:	2		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Style:	Cylinder- removable		
Shade/Diff. Material:	Top: Frosted white matte acrylic		
	Bottom Shade: Exterior powder-coated to match Device Green matte finish. Bottom Shade Interio match RAL 9010 Pure White matte finish		
Shade/Diff. Dims.:	3 1/8"Dia x 6 5/8"H		
Mounting Instructions:	Wall mounted, refer to architectural drawings fo and location	r mounting height	
Notes:	Manufacturer to provide mounting hardware and	l accessories	







Backplate & Base Finish

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample Shop Drawing**

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-204
Scheme:	A-Vibrant	Item Name:	Wall Sconce
Issue Date:	March-23	Area Name:	Public Area - Guest Corridors
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Manufacturer: Arkansas Lighting	Email: Δ9 hiltonsupport@arkansaslighting.com	Phone: Δ9 479.474.0876	

Instructions:

• All quantities to be verified by hotel operator prior to purchasing.

• It is the responsibility of the owner to interpret these specifications for each property.

• All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.

• Must be of contract quality and suitable for commercial use.

• All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.

• Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.

• Manufacturer/Fabricator to confirm weight of fixture.

• Manufacturer/Fabricator to verify installation method and hanging points.

• Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.

• Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-205
Scheme:	A-Vibrant	Item Name:	Pendant Lighting
Issue Date:	March-23	Area Name:	Public Area - Reception
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	3 Light Linear Pendant with Adjustable Height Core	ding	
Overall Dimensions:	45"W x 11"H x 13.5"D		
Finish:	Exterior: Powder-coated stainless steel to match RAL 170 40 40 Device Green matte finish. Interior: To match RAL 9010 Pure White		
Switch Type:	Hardwired		
Cord Length:	72", adjustable in field		
Cord Color:	Black cloth cord cover		
Lamp Type:	A15 LED, E26 Medium Socket 3000K Dipped Bulb		
Lamp Wattage:	11W	<u> </u>	
Lamp Quantity:	3	L	
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Style:	Bell shape fixture, open at bottom		
Shade/Diff. Material:	Powder-coated stainless steel		
Shade/Diff. Dims.:	13.5"Dia x 8"H		
Suspension Info:	Refer to architectural drawings for mounting heigh	t and location	
Notes:	Manufacturer to provide mounting hardware and a	ccessories	Exterior Finish

Interior Shade Finish

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample** Shop Drawing

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-205
Scheme:	A-Vibrant	Item Name:	Pendant Lighting
Issue Date:	March-23	Area Name:	Public Area - Reception
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Manufacturer: Arkansas Lighting	Email: Δ9 hiltonsupport@arkansaslighting.com	Phone: Δ9 479.474.0876	

• Must be of contract quality and suitable for commercial use.

• All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.

• Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.

• Manufacturer/Fabricator to confirm weight of fixture.

• Manufacturer/Fabricator to verify installation method and hanging points.

• Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.

• Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-206
Scheme: Issue Date:	A-Vibrant March-23	Item Name:	Table Lamp
		Area Name:	Public Area - TV Lounge
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Cylinder Style Lamp with Ring Accents and a To Outlets at the Base	p Shade including	
Dimensions:	7" Dia. (at Base) x 12"D x 23"H		
Finish:	Lamp Body: To match RAL 9011 Graphite Black Base: To match Tiger Drylac Sparkle Silver Gloss	-	
Switch Type:	On/Off Accessible rocker switch at base, Finish:	Black	
Cord Length:	72"		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement		
Lamp Type:	A15 LED, E26 medium socket 2700K		
Lamp Wattage:	8.5W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diffuser Style:	Tapered drum shade		
Shade/Diff. Material:	White linen wrapped shade with rolled edges		
Shade/Diff. Dims.:	Top: 11" Dia.; Bottom: 12"Dia.; Height: 10"		
Lamp Base:	Base to feature felt protective non-skid padding Base to be weighted.	secured to bottom.	Lamp Body Finish
Dimmer:	No		and the second sec
Notes:	Two outlets and 1USB-A and 1 USB-C ports to b base.	e integrated into the	

Base Finish

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample** Shop Drawing

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-206
Scheme:	A-Vibrant	Item Name:	Table Lamp
Issue Date:	March-23	Area Name:	Public Area - TV Lounge
Revisions:	May-23 Δ1; Dec-23 Δ4; Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Manufacturer: Arkansas Lighting	Email: Δ9 hiltonsupport@arkansaslighting.com	Phone: Δ9 479.474.0876	

• Manufacturer/Fabricator to verify installation method and hanging points.

• Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.

• Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-250
Scheme:	A-Vibrant	Item Name:	Lamp @ Perch Table
Issue Date:	May-23	Area Name:	Public Area - Lobby
Revisions:	Dec-23 Δ4; Sept-24 Δ9		RENO ONLY
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	Down Light Table Lamp with Outlets and USB for	or Charging	
Overall Dimensions:	12"W x 14"H x 3"D		
Finish:	Powdercoated stainless steel exterior to match RAL 9001 Graphite Black matte finish		
Switch Type:	On/Off Accessible rocker base switch at base. F	inish: Black	
Cord Length:	96"		
Cord Color:	Clear/Silver		
Plug Type:	90° plug with 45° cord placement	S. S. S. S. S.	
Lamp Type:	LED, PL, E26 Medium Socket 2700K		
Lamp Wattage:	6W		
Lamp Quantity:	1		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Material:	Powdercoated stainless steel shade to match RAL 9011 Graphite Black matte finish with frosted white acrylic diffuser		
Shade/Diff. Dims.:	3"W x 10 1/2"L		
Lamp Base:	Base to feature felt protective non-skid padding secured to bottom. Base to be weighted.		
			Lamp Body Finish
Dimmer:	No		
Notes:	To have two USB outlets, 1 - USB-C and 1 USB-	A	

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample Shop Drawing**

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.
- Manufacturer to clearly mark each carton with item ID and specification number.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-251
Scheme:	A-Vibrant	Item Name:	Pendant Light @ Re-Upholstered
Issue Date:	December-23		Banquette
Revisions:	Sept-24 Δ9	Area Name:	Public Area - Lobby RENO ONLY
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighitng.com	870.972.1177	
Description:	3 Light, Linear Pendant with Adjustable Height Cor	ding	
Overall Dimensions:	98"W x 36"H x 20"D	a tan	بطع
Finish:	Powder-coated stainless steel exterior to match RAL 9011 Graphite Black matte finish, interior to match RAL 9010 Pure White		
Switch Type:	Hardwired		
Cord Length:	84", adjustable in field		
Cord Color:	Black cloth cord cover		
Lamp Type:	A15 LED, E26 Medium Socket 3000K Dipped Bulb		
Lamp Wattage:	11W		
Lamp Quantity:	3		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Style:	Bell shape fixture, open at bottom		
Shade/Diff. Material:	Powder-coated stainless steel		
Shade/Diff. Dims.:	20"Dia x 7 1/2"H		Exterior Finish
Suspension Info:	Refer to architectural drawings for mounting heigh	t and location	
Notes:	Manufacturer to provide mounting hardware and a	ccessories	

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication: **Finish Sample** Shop Drawing

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00

Instructions:

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.

Interior Finish



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	(A) PA-251
Scheme:	A-Vibrant	Item Name:	Pendant Light @ Re-Upholstered
Issue Date:	December-23		Banquette
Revisions:	Sept-24 ∆9	Area Name:	Public Area - Lobby RENO ONLY

• Manufacturer to clearly mark each carton with item ID and specification number.