




Project Name:	Home2 Prototype FF&E Specifications	Item Number:	<b>(B) PA-251</b>
Scheme:	B-Dynamic	Item Name:	Pendant Light @ Re-Upholstered Banquette
Issue Date:	December-23	Area Name:	Public Area - Lobby <b>RENO ONLY</b>
Revisions:	Sept-24 Δ9		
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighting.com	870.972.1177	
Description:	3 Light, Linear Pendant with Adjustable Height Cording		
Overall Dimensions:	98"W x 36"H x 20"D		
Finish:	Powdercoated stainless steel exterior to match Benjamin Moore Blue Hydrangea 2062-60 matte finish, interior to match RAL 9010 Pure White		
Switch Type:	Hardwired		
Cord Length:	84", adjustable in field		
Cord Color:	Black cloth cord cover		
Lamp Type:	A15 LED, E26 Medium Socket 3000K Dipped Bulb		
Lamp Wattage:	11W		
Lamp Quantity:	3		
UL Listing:	Fixture must be U.L. listed and so labeled		
Shade/Diff. Style:	Bell shape fixture, open at bottom		
Shade/Diff. Material:	Powdercoated stainless steel		
Shade/Diff. Dims.:	20"Dia x 7 1/2"H		
Suspension Info:	Refer to architectural drawings for mounting height and location		
Notes:	Manufacturer to provide mounting hardware and accessories		



Exterior Finish



Interior Finish

Unless Using A Specified Manufacturer, Submit The Following Required Item(s) for Approval Prior to Fabrication:

**Finish Sample** ☐ **Shop Drawing** ☐

Manufacturer to confirm the Product meets Hilton Design and Construction Standards as noted in Section 2515.00

Instructions:

- All quantities to be verified by hotel operator prior to purchasing.
- It is the responsibility of the owner to interpret these specifications for each property.
- All interpretations of the specification MUST be submitted to Hilton Design Review (projecthub.hilton.com) for final approval prior to purchasing or implementation of any material.
- Must be of contract quality and suitable for commercial use.
- All materials and methods of construction must comply with all local fire and life safety codes and Brand Standards.
- Fixture must be U.L. Listed and so labeled. Manufacturer is responsible for submitting all technical specifications for fire safety, UL standards, and any other specifications that are required to comply with local and state fire codes.
- Manufacturer/Fabricator to confirm weight of fixture.
- Manufacturer/Fabricator to verify installation method and hanging points.
- Show all pieces in scaled shop drawings. Entire fixture shall be inspected during the manufacturing and again after final assembly.



Project Name:	Home2 Prototype FF&E Specifications	Item Number:	<b>(B) PA-251</b>
Scheme:	B-Dynamic	Item Name:	Pendant Light @ Re-Upholstered Banquette
Issue Date:	December-23		
Revisions:	Sept-24 Δ9	Area Name:	Public Area - Lobby <b>RENO ONLY</b>
Manufacturer:	Email: Δ9	Phone: Δ9	
Arkansas Lighting	hiltonsupport@arkansaslighting.com	479.474.0876	
Illumination Lighting	info@illuminationlighting.com	514.634.7200	
Trinity Lighting	hilton@trinitylighting.com	870.972.1177	

- Manufacturer to clearly mark each carton with item ID and specification number.